

AMIKO HD8265+ COMBO HD DVB-T2



Ocjena: Nije još ocijenjeno

Cijena

Cijena: 90,00 €

[Postavite pitanje o ovom proizvodu](#)

Opis

Tuner & Demodulation

Tuner Type: DVB-S / DVB-S2

Input Connector: F-type, Connector, Female

Signal Level: -65 to -25 dBm

LNB Power & Polarization: Vertical: +13V/+14V, Horizontal: +18V/+19V

Current: Max. 400mA (Overload Protection)

22KHz Tone Frequency: 22±1KHz

DiSEqC Control: Version 1.0, 1.1, 1.2, USALS

Demodulation: QPSK, 8PSK

Input Symbol Rate: 2-45 Mbps,

FEC: 1/2, 2/3, 3/4, 5/6, 7/8 and Auto

Tuner Type: DVB-T2 / DVB-C

Frequency Range: 48~862MHz

RF Input Level: -80dBm to -20dBm

Antenna power output: DC 5V at max 75mA, Overload protection

Demodulation: COFDM 1K, 2K, 4K, 8K normal and extended, 16K normal and extended, 32K normal and extended

Input Symbol Rate: 1.0 ~ 7.0Ms/s

Constellations: QPSK, 16QAM, 64QAM, 256QAM / Both rotated and non-rotated

Guard Intervals: 1/4, 19/256, 1/8, 19/128, 1/16, 1/32, 1/128

Code Rate: 1/2, 3/5, 2/3, 3/4, 5/6

MPEG TS A/V Decoding

Transport Stream: MPEG-2, H.264, H.265

Input Rate: Max.120Mbit/s

Aspect Ratio: 4:3, 16:9, Letter Box

Video Decoding: MPEG-4/H.265 [SP@L3 to ASP@L5](#), AVC, [HP@level 4.1](#), [MP@level 4.1](#)

Video Resolution: 720*480P/I, 720*576P/I, 1280*720p, 1920*1080i, 1920*1080p

Audio Decoding: MPEG-1/2,AAC-LC,HE-AAC,MP3,Dolby Digital

Audio Mode: Left / Right / Stereo/ Mono

Sampling Rate: 32, 44.1 and 48KHz System Resources

Main Processor: 800MHz CPU

Flash Memory: 16MB

DDR3 RAM: 256MB

Power Supply

Input Voltage: 12VDC

Power Consumption: 24W Max

Stand-By Power Consumption: <0.5W

A/V & Data Input/Output

RCA: Jack-type, CVBS Video out, L&R Audio out

RS-232C: Jack-type, Transfer rate 115.2Kbps, 9 pin D-sub Type

USB: Two USB 2.0 slots

S/PDIF: Optical

HDMI: VER1.4, Type A

Ethernet: 10/100M RJ45

IR IN: Jack-type, External IR sensor connection

Physical Specifications

Size: 180mm x 43mm x 155mm

Net Weight: 1.0KG

Operation Temperature: 0°C~+45°C

Storage Temperature: -10°C~+70°C

Storage Humidity: 5%~95% RH (Non-Condensing)

Channel Recording & Timeshifting Simultaneously (optional)

Channel switching time less than 1 second

True-color, User Friendly On-Screen Display (OSD)

Full Picture In Graphic (PIG) function

Electronic Program Guide (EPG)

Subtitle supported

Teletext supported with VBI insertion

Parental lock facility by channel and program event

Program and Channel information transfer from receiver to receiver

Satellite Blind Scan & Fast Scansupport

DiSEqC 1.0, 1.1, 1.2 and USALS Compatible

Full HD (1080p) Output via HDMI

Exciting games embedded

Multi-Language support

Software upgrade support via USB, Network, OTA, RS232

Power Consumption in Stand-By: <0.5W

Recenzije

Trenutno nema recenzija za ovaj proizvod.