

KABEL COAX GETI 121CU PE 5mm BLACK 100m



Ocjena: Nije još ocjenjeno

Cijena

Cijena: 65,00 €

[Postavite pitanje o ovom proizvodu](#)

Opis

- inner conductor: pure copper, \varnothing 0.80mm \pm 0.01
- first screen: overlapped Cu foil: \varnothing 3,57mm \pm 0.05
- second screen: bare copper, 72 x 0,10 mm
- braid diameter: 4,05mm \pm 0,05
- dielectric: \varnothing 3,50mm \pm 0,05
- sheath: PE black, \varnothing 5,0mm \pm 0,10
- nominal impedance: 75 Ω \pm 3
- capacity: 53 pF / km \pm 2
- maximum voltage: 2kV
- return loss: > 20 dB (5-2500 MHz)
- minimum static bend radius: 50mm
- velocity ratio: 84% (+/-2)
- operating temperature: -30 $^{\circ}$ C ? + 60 $^{\circ}$ C ?
- storage temperature: -30 $^{\circ}$ C ? + 70 $^{\circ}$ C ?
- packaging: 100 m reel = 1pc
- packing quantity: 2pcs carton box

Attenuation MHz / dB / 100 m:

- 5MHz - 1.7dB
- 50MHz - 5.3dB
- 100MHz - 7.5dB
- 200MHz - 10.5dB
- 400MHz - 15.0dB
- 600MHz - 18.8dB
- 800MHz - 21.9dB
- 1000MHz - 24.9dB

- 1350MHz - 28.9dB
- 1600MHz - 31.8dB
- 1750MHz - 33.3dB
- 2150MHz - 37.3dB
- 2400MHz - 39.6dB

Technical parameters

Use: outdoor

Attributes required: 100% copper, copper shielding, double shielding

Wire diameter: 5,0mm

Packaging: 100m

Recenzije

Trenutno nema recenzija za ovaj proizvod.