

## KABEL COAX GETI 121AL PVC 5mm WHITE 100m



Ocjena: Nije još ocjenjeno

**Cijena**

Cijena: 55,00 €

[Postavite pitanje o ovom proizvodu](#)

### Opis

- inner conductor: pure copper,  $\varnothing$  0.80mm  $\pm$  0.01
- first screen: overlapped Cu foil:  $\varnothing$  3.62mm  $\pm$  0.05
- second screen: tinned copper, 72 x 0,10 mm
- braid diameter: 4,02mm  $\pm$  0,05
- dielectric:  $\varnothing$  3,50mm  $\pm$  0,05
- sheath: PVC white,  $\varnothing$  5,0mm  $\pm$  0,10
- nominal impedance: 75  $\Omega$   $\pm$  3
- capacity: 53 pF / km  $\pm$  2
- maximum voltage: 2kV
- return loss: > 20 dB (5-2500 MHz)
- minimum static bend radius: 25mm
- velocity ratio: 84% (+/-2)
- operating temperature: -30  $^{\circ}$ C  $\pm$  60  $^{\circ}$ C
- storage temperature: -30  $^{\circ}$ C  $\pm$  70  $^{\circ}$ C
- packaging: 100 m reel = 1pc
- packing quantity: 2pcs carton box

Attenuation MHz / dB / 100 m:

- 5MHz - 1.7dB
- 50MHz - 5.6dB
- 100MHz - 7.7dB
- 200MHz - 10.9dB
- 400MHz - 15.8dB
- 600MHz - 19.6dB
- 800MHz - 22.6dB
- 1000MHz - 25.1dB

- 1350MHz - 29.2dB
- 1600MHz - 32.6dB
- 1750MHz - 34.8dB
- 2150MHz - 37.8dB
- 2400MHz - 40.9dB

#### Recenzije

Trenutno nema recenzija za ovaj proizvod.