

KABEL COAX GETI 125AL PVC 7mm WHITE 100m



Ocjena: Nije još ocjenjeno

Cijena

Cijena: 80,00 €

[Postavite pitanje o ovom proizvodu](#)

Opis

- inner conductor: pure copper, \varnothing 1,00mm \pm 0,01
- first screen: overlapped Al foil: \varnothing 4,92mm \pm 0,05
- second screen: tinned copper, 72 x 0,10 mm
- braid diameter: 5,32mm \pm 0,05
- dielectric: \varnothing 4,80mm \pm 0,05
- sheath: PVC white, \varnothing 6,8mm \pm 0,10
- nominal impedance: 75 Ω \pm 3
- capacity: 55 pF / km \pm 2
- maximum voltage: 2kV
- return loss: > 20 dB (5-2500 MHz)
- minimum static bend radius: 65mm
- velocity ratio: 84% (+/-2)
- operating temperature: -30 $^{\circ}$ C ? + 60 $^{\circ}$ C ?
- storage temperature: -30 $^{\circ}$ C ? + 70 $^{\circ}$ C ?
- packaging: 100m = 1pc
- packing quantity: 2pcs carton box

Attenuation MHz / dB / 100 m:

- 5MHz - 1.8dB
- 50MHz - 4.7dB
- 100MHz - 6.3dB
- 200MHz - 8.8dB
- 400MHz - 12.6dB
- 600MHz - 15.6dB
- 800MHz - 18.2dB
- 862MHz - 18.8dB

- 1000MHz - 20.1dB
- 1350MHz - 23.5dB
- 1750MHz - 27.4dB
- 2400MHz - 33.0dB

Technical parameters

Use: interior

Attributes required: 100% copper, copper shielding, double shielding

Wire diameter: 6,8mm

Packaging: 100m

Recenzije

Trenutno nema recenzija za ovaj proizvod.