

EDISION PICCOLLINO COMBO S2+T2/C

Ocjena: Nije još ocijenjeno

Cijena

Cijena: 55,00 €

[Postavite pitanje o ovom proizvodu](#)

Opis

PICCOLLINO S2+T2/C is the new compact EDISION H.265/HEVC 10 Bit COMBO receiver with Card Reader, two tuners, one satellite for DVB-S & S2 and one HYBRID for DVB-T/T2 and DVB-C. It features new processor for fast menu and channel selection, while it can store up to 6000 channels. The LAN port at 100Mbps offers access to web applications and along with its Media Player functions, in combination with its elite 2-in-1 IR remote control for the receiver and 5 TV functions, it will provide you with even more fun and enjoyment of your favourite programmes and functions. Of course, it comes with the trusted EDISION guarantee and support.

Technical Features:

- Type: Digital Combo Receiver for DVB-S2, DVB-T2 and DVB-C H.265/HEVC 10 Bit
- Full HD H.265/HEVC decoding support (covered by patents listed at patentlist.hevcadvance.com)
- Resolution: 480p, 576p, 720p/50Hz, 720p/60Hz, 1080i/50Hz, 1080i/60Hz, 1080p/50Hz, 1080p/60Hz TV Standard
- 2-in-1 IR remote control for the receiver and 5 TV functions.
- DiSEqC 1.2, 13/18V, 0/22K, LNB
- Unicable & SCR Unicable 2 support
- 1 x Card Reader
- 1 x HDMI output for High definition video/audio.
- 1 x Ethernet RJ45 10/100 Mbps port
- 1 x AV out (jack)
- 1 x IR in (jack)
- 1 x RS232 (jack)
- 1 x S/PDIF output
- 2 x USB
- 1 x LED Display
- LNB in
- 6000 TV/Radio channels memory.
- PAL/NTSC auto-switch
- Multilingual OnScreenDisplay.
- EDIVISION electronic program guide
- Supports Picture In Grafik (PIG)
- Channel Edit and Favourite Lists
- Auto and Manual channel search
- Auto-timer ?n/Off
- Wifi Connection (with USB Dongle)

- 3G Connection (with USB 3G Modem)
- PVR via USB
- ?ime Shift function
- Subtitle support
- Teletext support
- Last channel auto save
- Software upgrade & backup/channel list, via USB.
- Media player MP3/JPEG/BMP/AVI/DivX/VOB/MKV
- Supports FAT 16/32, NTFS
- Parental control

Applications:

- Youtube
- RSS News
- Weather Forecast
- Web Server

Front Panel:

- Display: LED
- 1 x Smartcard slot
- Display Buttons: Power, Channel +/-

Side Panel:

- 2 x USB 2.0 slot

Back Panel:

- Input Sat-IF: 1x F-type
- Input ANT-IN: 1x IEC-type
- Connection TV: 1x HDMI, AV out (jack)
- Video output: 1x HDMI, 1x Analog Video
- Audio output: Coaxial (S/PDIF), Analog R/L (jack)
- 1 x Ethernet plug
- 1 x Jack to RS232
- 1 x Jack to IR
- 1 x DC for Power Supply

Package includes:

- 2-in-1 IR remote control for the receiver and 5 TV functions.
- 12v external power supply unit
- Jack to RCA cable
- Jack to Infrared cable
- 2 x "???" batteries
- Mini Manual GR/EN/DE

General:

- Power Supply: 100 - 240 AC 50/60Hz
- Input Voltage: DC 12V 1.5A
- Power Consumption: max. 15.0W
- Power Consumption in standby: <0.5W
- Operating Temperature: 0°C ... +50°C
- Storage Temperature: -20°C ... +70°C
- Humidity Range: 10% ... 85% RH, non-condensing
- Dimensions: (W x H x D): 145x120x35 (mm)
- Weight: 0,5 kg
- Color: black

Recenzije

Trenutno nema recenzija za ovaj proizvod.