

AMIKO X-FINDER 3 DVBS2/T2/C



Ocjena: Nije još ocjenjeno

Cijena

Cijena: 350,00 €

[Postavite pitanje o ovom proizvodu](#)

Opis

https://www.amikohome.com/api/file/f/338/webleaflet_eng_xfinder_3_20190305-pdf

Satellite, T2/T Terrestrial and Cable Signal Measurement

Full feature portable set-top box

7" color display

One Conax Embedded card reader

One Common Interface Slot

BNC for analogue camera input

Satellite Blind Scanning support

Spectrum Analyzer

Satellite Dish Angle calculation

Constellation measurement

Dynamic Error Rate Calculation & Display

High Speed USB 2.0 connection

Multimedia playback (MP3, MP4, MKV, AVI, MPG, etc...)

Ethernet Connection

USB WiFi support (Ralink RT5370 chipset)

Full HD (1080p) video output via HDMI

DC 12V output connection

Unicable & DiSEqC 1.0, 1.1, 1.2 & USALS support

Remote Controller included

Car Charger included

Two handles for both left and right handed use

Built-in kickstand

Easy Database Management and Transfer via USB

Easy Software Upgrades through USB & Internet

MAIN FEATURES

MORE FEATURES

System Resources

Main Processor: 800 MHz based CPU

Flash Memory: 64 Mbits

DDR RAM: 2048 Mbits

Satellite Tuner

Tuner Type: DVB-S / DVB-S2

Input Connector: F-Type connector, female

Frequency Range: 950MHz - 2150MHz

Signal level: -65 to -25dBm

LNB Power & Polarization: Vertical: +13V

Horizontal: +18V

Current: 300mA max

Overload protection

22KHz Tone: 22 ± 1 KHz

DiSEqC Control: Amplitude: 0.6 ± 0.02 V

Version 1.0, 1.1, 1.2, USALS

Demodulation: QPSK, 8PSK

Input Symbol Rate: 2-45Mbps, Convolution Code Rate

FEC: 1/2, 2/3, 3/4, 5/6, 7/8, 1/4, 1/3, 2/5, 3/5, 4/5, 8/9,

9/10

Terrestrial Tuner

Tuner Type: DVB-T / DVB-T2

Input Connector: IEC-Type connector, female

Signal Level: Nordig Compliant, DBOOK Compliant

FEC: DVB-T: Viterbi + Reed Solomon 1/2, 2/3, 3/4, 5/6,

7/8

DVB-T2: LPDC + BCH 1/2, 3/5, 2/3, 3/4, 5/6

Frequency Range: 47-862MHz

Demodulation: QPSK, 16QAM, 64QAM, 256QAM (both rotated and non-rotated)

Guard Interval: 1/4, 19/256, 1/8, 19/128, 1/16, 1/32, 1/128

FFT Mode: 1k, 2k, 4k, 8k, 16k, 32k normal and extended

Channel Bandwidth: 6 / 7 / 8MHz

Antenna Output Power: 5V 50mA max

Demodulation: COFDM 2K/8K

Cable Tuner

Tuner Type: DVB-C

Input Connector: IEC-Type connector, female

Frequency Range: 47-862MHz

Signal Level: -20dBmV - +20dBmV

Bandwidth: 8MHz

Demodulation: 16QAM, 32QAM, 64QAM, 128QAM, 256QAM

Input Symbol Rate: 1.5 - 7Ms/s

MPEG TS A/V Decoding

Transport Stream: MPEG-2, H.265

Input Rate: Max 120Mbit/s

Aspect Ratio: 4:3, 16:9

Video Decoding: MPEG-2, MP@ML, MPEG-4 part10/H.264, H.265

Audio Decoding: MPEG-1 layer I/II, MPEG2 layer II, Dolby Digital,

AAC

Audio Mode: Left, Right, Stereo, Mono

Sampling Rate: 32, 44.1, 48KHz

A/V & Data Input / Output

Video In: BNC type, analogue video input

USB: High Speed USB2.0 connection (Type A)

HD OUT: HDMI Ver 1.3, Type A

Ethernet: RJ45 10/100M

Power Supply

Input Voltage: AC 100-240V 50/60Hz

Output Voltage: DC 12V 4.5A max

Power Consumption: 48W max

Battery: 7.4V 6.3Ah

Battery Charging Time: 3.5 hours

Battery Discharging Time: up to 6-7 hours

Physical Specifications

LCD Display: 7 inch

Size: 275mm x 175mm x 50mm (WxHxD)

Recenzije

Trenutno nema recenzija za ovaj proizvod.